



EMERGENCY ROAD SERVICES TIRE PERFORMANCE TIPS PEOPLE, PICS & EVENTS FOR THE PRESS CONTACT US

**TRUCK TIRES**

WHAT TIRE WILL WORK BEST FOR ME?

LOAD / PSI TABLES & TIRE INFORMATION

RECORDKEEPING FORMS

OWN AN RV?

TELL US WHAT YOU THINK!

REQUEST A CATALOG

TRUCKING LINKS

OTHER WEB SITES



**FIRESTONE TRUCK TIRES**

{ TIRE SELECTOR }

**T831**  
Extreme service drive


Ideal application:  
On/Off Highway

Designed for severe on/off-highway drive axle applications.

Extra-deep 31/32" tread for very long original tread life and excellent soft-surface traction.

Special tread compound resists cutting, chipping and chunking.

Open shoulders and aggressive center lugs provide outstanding traction on and off highway.



Compares to: Continental HDC / HDO Yokohama LY053 / TY063

Tire Size	Article Number	Load Rng.	Ply Rating	Meas. Rim	Tread Depth	Weight	Overall Diameter	Overall Width	Overall Width [loaded]	Static Loaded Radius	Revs Per Mile	Load Limit Single	Load Limit Dual	Max. Speed
					32nds/mm	lbs/kg	in/mm	in/mm	in/mm	in/mm	rpm/rpk	lbs@psi/kg@kpa		mph/kph
11R22.5	281557	H	16	8.25	31	136.2	42.4	10.7	11.8	19.7	490.0	6610@120	6005@120	55
					metric:	25	61.8	1077	272	300	304	3000@830	2725@830	88
12R22.5	281581	H	16	9.0	31	150.0	43.6	11.4	12.7	20.2	476.0	7390@120	6780@120	55
					metric:	25	68.0	1107	290	323	296	3350@830	3075@830	88
11R24.5	281565	H	16	8.25	31	142.1	44.5	10.7	11.8	20.8	467.0	7160@120	6610@120	55
					metric:	25	64.5	1130	272	300	290	3250@830	3000@830	88
10.00R20	281549	H	16	7.5	31	135.3	42.3	10.8	11.8	19.7	491.0	6610@120	6005@120	55
					metric:	25	61.4	1074	274	300	305	3000@830	2725@830	88
11.00R20	281573	H	16	8.0	31	161.12	43.5	11.4	12.5	20.2	478.0	7390@120	6780@120	55
					metric:	25	73.1	1105	290	318	297	3350@830	3075@830	88

Date: 08/09/2007

© 2006-2007 BFNT, LLC | legal notice