



MILITARY TIRES

Tire Size	Load Range	Single Load		Single Inflation		Dual Load		Dual Inflation		Weight		Rim Width	Overall Width		Overall Diameter		Static Radius		RPM	KPM	Tread Depth	Min. Dual Spacing		Speed Rating
		lbs	kg	psi	kpa	lbs	kg	psi	kpa	lbs	kg	in	in	mm	in	mm	in	mm			32nds	in	mm	
G177™																								
TUBE TYPE TIRES ON TYPE I, II AND III RIMS																								
11.00R20	H	7,390	3,350	120	830	6,780	3,075	120	830	160	73	8.00	11.4	290	43.7	1,110	20.5	521	478	297	33.0	13.2	335	68
AT-2A™																								
TUBELESS TIRES ON 5° TAPERED OR TYPE III TUBELESS RIMS																								
14.00R20	J	9,960	4,525	100	700	8,740	3,970	90	620	265	120	10.00	15.2	386	49.2	1,250	22.4	569	427	265	30.0	17.7	450	55
16.00R20	M	14,540	6,600	110	750	N/A	N/A	N/A	N/A	332	151	10.00	17.1	434	52.1	1,323	23.7	602	403	250	33.0	20.2	513	55
16.00R21	M	14,540	6,600	110	750	N/A	N/A	N/A	N/A	336	152	10.00	17.1	434	52.1	1,323	23.7	602	403	250	33.0	20.2	513	55
AT-3A™																								
TUBELESS TIRES ON 5° TAPERED OR TYPE III TUBELESS RIMS																								
16.00R20	M	14,540	6,600	110	750	N/A	N/A	N/A	N/A	342	155	10.00	17.4	442	51.6	1,311	22.8	578	407	253	33.0	20.2	513	55
MV/T™																								
TUBELESS TIRES ON 5° TAPERED OR TYPE III TUBELESS RIMS																								
395/85R20	G	9,370	4,250	95	660	N/A	N/A	N/A	N/A	210	95	10.00	15.4	391	46.6	1,184	21.5	546	446	277	26.0	N/A	N/A	68

